

Tripp-Lite Power Conditioners and UPS Systems

Pure Sine Wave and Automatic Voltage Regulation



HTR22-2U



HTR05-1RU and HTR07-1RU



HT1000UPS



HTRL15UPS

Tripp Lite's Pure Sine Wave UPS Systems generate perfect power and provide the highest level of protection and support for audio and video components. The Pure Sine Wave double-conversion process resynthesizes incoming AC power into a pure sine wave output, with zero transfer time to battery. This ensures exceptionally clean and pure power without output delay in the event of an incoming AC power loss or anomaly. In addition, Tripp Lite's UPS systems feature IP addressability and PC monitoring for complete system integration.

FEATURES & BENEFITS

- Pure Sine Wave Power or Automatic Voltage Regulation
- IP Addressable/Remote Diagnostics Capability
- Individual Outlet Control
- Phone/DSL, Ethernet and Coaxial Protection
- Battery Backup & Surge/Spike Protection
- EMI/RFI Filtering
- Power Alert PC Software for Real-time Diagnostics & Monitoring
- LED Diagnostics or LCD Display
- Up to \$250,000 Guaranteed Protection
- AMX and Crestron Integration Partner

Model	Outlets	Voltage Regulation	Guaranteed Surge Protection (Insurance)	Battery Backup Time During Blackouts (Recording/Viewing)*	Optional External Battery Packs (Sold Separately)	Output Capacity (VA/Watts)	Rack Space	Communication Ports (for Media Center)	Included Signal-Line Protection	Optional Signal-Line Protection (Sold Separately)	SNMP/Web Accessory Slot	Unit Dimensions** (H x W x D (in))
HTR22-2U	7	Pure Sine Wave	\$250,000	16 hr./90 min. +	Yes	2200/1600	2U	1 USB & 1 DB9	1 (Tel/Ethernet)	Yes	Yes	3.5 x 17.5 x 19
HTR15-2U	6	Pure Sine Wave	\$250,000	12 hr./60 min. +	Yes	1500/1200	2U	1 USB & 1 DB9	1 (Tel/Ethernet)	Yes	Yes	3.5 x 17.5 x 19
HTR10-2U	6	Pure Sine Wave	\$250,000	9 hr./45 min. +	Yes	1000/800	2U	1 USB & 1 DB9	1 (Tel/Ethernet)	Yes	Yes	3.5 x 17.5 x 14
HTRL15UPS	8	Automatic Voltage Regulation	\$250,000	5 hr./20 min.	-----	1500/900	2U	1 USB & 1 DB9	1 (Tel/Ethernet) 3 (Coax)	Yes	-----	3.5 x 17.25 x 10.5
HT1000UPS	8	Automatic Voltage Regulation	\$100,000	3 hr./15 min.	-----	1000/500	2U	1 USB	1 (Tel) & 2 (Coax)	Yes	-----	3.5 x 12 x 6.5
HTR07-1U	6	Automatic Voltage Regulation	\$250,000	6 hr./25 min.	-----	750/450	1U	1 USB & 1 DB9	-----	Yes	Yes	1.75 x 17.5 x 16.75
HTR05-1U	7	Automatic Voltage Regulation	\$250,000	2 hr./10 min.	-----	500/300	1U	1 USB & 1 DB9	-----	Yes	Yes	1.75 x 17.5 x 11.75

* Backup times will vary depending on battery condition and load. Since viewing requires substantially more power than recording, battery runtimes are different. All models are rated to 120V (60 Hz) operation, except HTR22-2U, HTR15-2U and HTR10-2U, which also accept 50 Hz frequency. ** MOUNTING OPTIONS: Rackmount: HTR22-2U, HTR15-2U, HTR10-2U, HTR07-1U AND HTR05-1U (mount to rack using included hardware). HT1000UPS (optional rack shelf available separately) Tripp Lite Model #s SR201 or SR206.



HTR15-2U REAR PANEL